

The Ultimate High Performance Cutting Lubricant

JET9 LX

Stoughcool's Jet9 LX is a moderate-to-heavy-duty hybrid micro-emulsion. Stoughcool Jet9 LX has a very tight emulsion for excellent tramp oil rejection keeping sumps and machines clean! Formulated for ferrous and non-ferrous materials and coupled with an EP lubricant, it's recommended to cut a wide range of materials. Stoughcool Jet9 LX utilizes our C80 Shield™ Technology making it bio-resistant against bacteria and mold and provides excellent sump life measured in years! Absolutely no sump stench, no bad odors!

Jet9 LX offers these advantages for:

- Extended sump life measured in years
- Excellent lubricity, excellent tool life
- Great for high pressure systems, low foaming
- No formaldehyde release biocides
- Uses C80 Shield™ Technology Eliminating sump stench
- Extremely stable even in hard water conditions
- For cutting ferrous and non-ferrous materials

STOUGHCOOL

WE KNOW COOLANT.

www.stoughcool.com

| | |
|--|------------------------------|
| Appearance | Yellow to Light Amber |
| PH@ 5% | 9.3 |
| Density lbs./gal. | 8.47 |
| Grinding Dilution Recommendation | 3%-to-6% |
| Machining Dilution Recommendation | 5%-to-10% |
| Refractometer Multiplier | 1.5 |



Stoughcool Jet9 LX does not contain nitrites, sulfur, formaldehyde-release biocides, phenolic biocides, triazine or DCHA. Not for use on Magnesium.